



GREENSOLV inc.

TECHNICAL BULLETIN

GREENSOLV 951 SOLVENT DEGREASER - dielectric

1) PRODUCT DESCRIPTION

GREENSOLV 951 is a very efficient solvent based degreaser with a moderate evaporation rate. It is used to clean oils, carbon deposits, inks, waxes, greases and tar on various types of parts and equipments. **GREENSOLV 951** leaves the surface dry and clean without need for rinsing with water. This product is great to clean and prepare a metal surface before applying a new coating. It is compatible with bare metals, painted surfaces, concrete, glass, rubber and plastics. The product can affect certain types of plastics; it is therefore recommended to proceed to a spot test before using it on such surfaces. **GREENSOLV 951** is a solvent with a very low electric conductivity (dielectric).

Typical applications

Surface cleaning – paint preparation
Electrical equipment degreasing
Soaking tank applications
Degreasing parts and equipments

Concentration of GREENSOLV 951

Pure
Pure
Pure
Pure

2) ADVANTAGES

Based on an elaborate blend of biodegradable and photodegradable solvents, with a low ozone depleting potential, **GREENSOLV 951** has a very low toxicity for the user.

Its main benefits are:

- Excellent degreaser for oils, carbon deposits, inks, waxes, greases and tar;
- Flash off solvent with moderate evaporation rate
- Dielectric
- Compatible with all bare metals, painted surfaces, concrete, glass, rubber and plastics
- Low ozone depleting potential
- Biodegradable

3) PHYSICAL PROPERTIES

Appearance	translucide orange liquid
Odour	citrus fruits
pH (Sol. 1%)	N/A
Flash point.....	40 -45°C
Specific gravity	0.75 – 0.85
Biodegradability	good

4) DIRECTIONS FOR USE

*Note: For best results, when using **GREENSOLV 951 on heavy contamination**, follow these tips for best results:*

- *Mechanical agitation with a rag or a brush will greatly improve the cleaning efficiency*
- *Agitation / recirculation of the product increases the efficiency of the cleaning solution*
- *A longer dwell time will be beneficial for dry contaminants.*

*Note: A solvent such as **GREENSOLV 951** can be used several times before becoming inefficient. In a soaking tank, depending on its usage, it can last anywhere from a few weeks to several months. Used in other applications, it can be recirculated or recycled.*

- Apply pure on the surface to be cleaned
- Let soak for a few moments
- Use mechanical agitation (brush or rag) as required
- Let dry.

5) PERSONAL PROTECTION

When using **GREENSOLV 951**, it is recommended to wear the following safety equipments:

- Safety glasses or goggles,
- Chemical resistant gloves.
- Wear appropriate respirator when ventilation is inadequate. (Approved/certified respirator with organic vapor cartridges.),

6) STORAGE

Store **GREENSOLV 951** at a controlled temperature below 30° C (50° F to 104° F) in a METAL CONTAINER. Store in a closed container when not in use. The shelf life of the product has been determined to be three (3) years.

7) PACKAGING

GREENSOLV 951 is available in following size containers:

- Pails (18,9 Litres/ 5 Gallons);
- Drums (205 Litres / 45 Gallons);

Version : 2
Last revision : April 2012